



# LG ProBeam BU53RG

for Business

## 4K Laser Projector with 0.94 Short Throw Ratio

BU53RG is a short throw business projector newly released in 2023. BU53RG is high-range projector featuring up to 5,000 ANSI Lumens of brightness, 4K UHD resolution, and a long lamp lifespan for hours of entertainment. Plus, the short focal length improves projector usability. With various connection methods, easy installation, and horizontal and vertical lens shift with x1.2 zoom, this projector is versatile enough for both museum and office environments, regardless of space restrictions. BU53RG provides application support for a host of signage companies in a variety of different environments.

### Key Features



High Brightness



Short focal length



Cost Saving



Ease of Use



Smart Connectivity

### Matching Vertical



Golf



Gallery



Museum



Enterprise




School

### Specification

Category			BU53RG
Projection System	Native Resolution		4K UHD (3840 x 2160)
	Brightness (ANSI Lumen) <sup>1)</sup>		5,000
	Contrast Ratio (Full On Full Off)		3,000,000:1 1
	Noise (typical)	Energy Saving Min. (Bright)	29 dB(A)
		Energy Saving Med.	27 dB(A)
		Energy Saving Max. (Eco)	26 dB(A)
	Uniformmerty(IBMMA 9point)		85%
	Projection Lens	Focus (Auto / Manual)	Manual
		Zoom	1.2x
	Projection Image	Screen Size	40"~300"
		Standard (lens to wall)	Wide 2017 / Tele 2454 (100")
	Throw Ratio		0.94~1.14
	Lens Shift		0 ( Horiz ± 20% / Vert ± 50% )
General Specification	Projection Offset		100%
	Light source	Type	Laser (LD + P/W)
		Life High Brightness	20,000 Hrs.
	OSD Language		Support Local Language
	Aspect Ratio Control		Full / Original
	Sound	Output	10W (5W+5W)
		Clear Voice	○ (Clear VoiceIII)
	Net Size (mm) (W x D x H)		370 x 290 x 155.7 / 370 x 290 x 143.7 (Without Leg)
	Net Weight (kg or g)		9.7KG
	Power Consumption (Max.)		380W
	Stand-by Power		0.5W <sup>1</sup>
	Power Supply		100V~240V @ 50~60 Hz (Built-in PSU)
	Operation Temperature		0 ~40°C
Input /Output Terminals	Input Signal Compatibility	Digital(HDMI)	Up to 4K (4096x2160) (60Hz, 50Hz, 24Hz)
	Audio out		○ (Phone Jack)
	RS-232C		○ (1In, 1 Out)
	IP control		○ (Crestron)
	RJ45		1
	HDMI		2
	USB Type-A		2 (USB2.0)
	Platform (OS, UI)		Signage webOS 6.0
Main Features	Screen Share (Wireless Mirroring with MiraCast supporting device)		○
	Content Sharing (with DLNA supporting device)		○

### Dimension



<sup>1)</sup> The brightness (Lumen) is based on the perceived brightness equivalent to the brightness of lamp projector